

## TECHNICAL SPECIFICATIONS – G6 Landscape 75 Digital Signage Stele

	SPECIFICATION	REMARK
Screen size	75"	
Temperature operation	-40°C to +55°C/-40°F to +131°F	Ambient temperature
Operating humidity	0% - 100%	Immunity to humidity
Intended area of installation	Full-outdoor	Direct sun exposed locations
Operation	24/7/365	
Intended LCD operation	24/7/365	G6 warranted LCD operation time
Dimensions	1.878mm x 2.182mm x 360mm	Width x Height x Depth
Weight	390 kg	Approximate
Bezel	90 mm	Top and side thickness
Display to glass distance	12 mm	Distance from LCD panel to protective glass
Orientation	Landscape	
Sides	Single	
Power consumption	1,0kW +- 20%	Depends on deployment area
Power supply	400 V, 3Φ, 50 Hz, 16 A	
Technical certification	UL/ CE/IP65 compliant	

---

## ESSENTIAL SYSTEM MODULES

---

### LCD PANEL

### FULL HD PROFESSIONAL LCD

---

Options

**Default**

LCD panel technology

**TFT**

Backlight type

**LED**

Brightness

**2.500**

Operation in NIT at 25°C inner enclosure temperature

Contrast

**5.000:1**

Aspect ratio

16:9 portrait

Resolution

1.920 x 1.080 px

Viewing angle

178° horizontal /178° vertical

Display area

1.650mm x 928mm

---

### ENCLOSURE SYSTEM

### G6

---

Ingress protection rating

IP66/ NEMA 4x

Hosting LCD display and electrical compartment

Material

Steel and aluminum

Steel enclosure and aluminum masks

Material handling

2 color coating (ground and cover layer)

RAL 9011 F.E. QC

Inner enclosure temperature fluctuation

Between 20°C and 25°C/68°F to 77°F

Stable room temperature is unique G6 trait!

Cooling and heating

Bespoke HVAC

HVAC module

Air circulation loop type

Closed system

Maximum isolation from environment

Dust and dirt entry protection

No entry points

Glass

4+4 mm tampered glass/ anti-reflective coating  
(AR)

0,5% reflection

---

Enclosure opening registration	Magnetic switch	Records opening
External connectors	2 x USB 2.0	Provides mouse and keyboard connectivity
	RJ-45	Provides access to display internal LAN
	Reset & shutdown buttons	Enables quick on-site reboot and shutdown
Internal connectors	RJ-45	Connects to internet
	BNC	Optional: composite video input
	4-pin Mini-DIN	Optional: S-video input
	AC socket	Appropriate for destination region
	Terminal block	Connects to mains AC electric power supply

## HVAC

## ADVANCED SILENT HEATING, VENTILATION AND AIR CONDITIONING UNIT

Compressor	3-phase heavy duty rotary compressor	Ensures reliability in extreme conditions as well as quiet operation
Type of regulation	Frequency controlled, based on pressure and temperature sensors	Ensuring a soft start, stable temperature, lower power consumption, longer lifespan and reduced maintenance
Advanced diagnostics	Pressure and temperature sensors	Ensuring proper HVAC operation and allowing error and status reporting as well as maintenance requests
Low temperature protection	Compressor heater for extreme conditions	Protects the compressor from extremely low temperatures

## INTELLIGENCE

## ECU G6 (ELECTRONIC CONTROL UNIT)

Fully programmable ECU and controlmotion G6 software	Emergency shutdown protection	Automatic shutdown of system in case of emergency
	High/low temperature protection	Integrated components work within specified temp. range
	Hot/cold sequential start-up	Sequential start-up of components in specified temp. range
	Display and sound control	Remote control of display and sound settings

Remote system health monitoring	Control and diagnostic software controlmotion G6	Free add-on software installed onto PC
	Control and diagnostic software ADVANCE	Payable add-on server software
	Data Logging	Collecting and saving performance data
	Remote PC restart	Remote restart when PC is working
	Remote PC ON/OFF	Remote on/off/restart when PC is not responding
	Health diagnostic data	Relevant system info data monitoring and collection
	Maintenance on-site call (No regular maintenance!)	Automatic maintenance call functionality
	Email reporting option	Automatic failure notifications (i.e. critical error, daily report)
	Remote monitoring (when PC off)	Alternative access to system is possible when PC off
	Data logging and storage (when PC off)	DATA from ECU G6 temporary storage enabled when PC off

## COMPUTER

### Player (Nexcom NDiS B533)

Processor	Intel® Core™ i5-4570TE (4M Cache, up to 3.30 GHz)
Memory	4 GB DDR3 1333 RAM (Options: up to 16 GB max)
Graphics	Intel HD Graphics 4600
Hard disc	320 GB SATA disk drive (Option: SSD)

Specifications and design are subject to change without notice.