

Outdoor Digital Signage Stele G7

TECHNICAL SPECIFICATION

Standard products

SYSTEM	TEMPERATURE OPERATION	-40C to +55C/-40F to 131F	INTELLIGENCE
	OPERATING HUMIDITY	0% - 100%	
	INTENDED AREA OF INSTALLATION	Full-outdoor	
	INTENDED OPERATION	24/7/365	
	POWER RATING	220-240 V; 50/60 Hz; 16A	
	WARRANTY	3 year warranty (5 year extension)	
ENCLOSURE	TECHNICAL CERTIFICATION	CE/IP66 certified	
	IK RATING	IK10 certified	
	MATERIAL	Steel and aluminum	
	MATERIAL HANDLING	2 color coating (ground and cover layer)	
	INNER ENCLOSURE TEMP. FLUCTUATION	20C to 25C/68F to 77F	
	COOLING AND HEATING	Advanced HVAC	
	GLASS	4+4 mm tempered glass/ anti-reflective coating (AR)	
	AIR CIRCULATION LOOP TYPE	Closed system	
	DUST AND DIRT ENTRY PROTECTION	No entry points	
	EXTERNAL CONNECTORS	2 x USB 2.0, Reset & shutdown buttons, RJ-45	
INTERNAL CONNECTORS	HDMI/Display Port, AC socket, Terminal block		
COMPUTER	PLAYER	Shuttle DS77U5	
	PROCESSOR	Intel® i5 - 7200U (2x 2.50 GHz)	
	MEMORY	4 GB DDR4 SO-DIMM (Up to 16 GB)	
	GRAPHICS	Intel HD 520 Graphics, DX 12	
	HARD DISK	SSD 120GB SATA3 disk drive (Up to 250 GB)	

- NO REGULAR MAINTENANCE!
- MAINTENANCE ON-SITE CALL
- EMERGENCY SHUTDOWN PROTECTION
- HIGH/LOW TEMPERATURE PROTECTION
- HOT/COLD SEQUENTIAL START-UP
- DISPLAY AND SOUND CONTROL
- CONTROL AND DIAGNOSTIC SOFTWARE CONTROL
- MOTION
- DATA LOGGING
- REMOTE PC RESTART, ON/OFF
- HEALTH DIAGNOSTIC DATA
- EMAIL REPORTING OPTION
- REMOTE MONITORING (WHEN PC OFF)
- DATA LOGGING AND STORAGE (WHEN PC OFF)

*Can be customized

TECHNICAL SPECIFICATION

Standard products

Size	Mou nting	Orien tation	Sides	Name	Dimensions (mm)	Weight (KG)	Bezel (mm)	Display to glass distance (mm)	Power consumption: Max / Typical (kW)	Default LCD Panel Standard & alternative		
55"	FS	P	Double	55 P2 FS	928 x 2336 x 461	300	191 / 90	20	2.50 / 1.30	Typical Brightness:	2500 nit	700 nit
		L		55 L2 FS	1444 x 2023 x 460	300	191 / 90	22	2.50 / 1.30	Typ. static contrast ratio:	5000:1	1300:1
	FS	P	Single	55 P FS	928 x 2336 x 360	260	191 / 90	20	1.55 / 0.85	Resolution:	1920x1080 px	
		L		55 L FS	1444 x 2023 x 384	260	191 / 90	22	1.55 / 0.85	Display area:	1210x680mm	
75"	FS	P	Double	75 P2 FS	1168 x 2556 x 476	530	195 / 90	16	3.90 / 2.10	Typical Brightness:	2500 nit	3000 nit
		L		75 L2 FS	TBD	530	110 / 90	28	3.90 / 2.10	Typ. static contrast ratio:	5000:1	12T00:1
	FS	P	Single	75 P FS	1168 x 2556 x 440	380	195 / 90	16	2.65 / 1.25	Resolution:	1920x1080px	3840x2160px
		L		75 L FS	1888 x 2230 x 476	380	110 / 90	28	2.65 / 1.25	Display area:	1650x928mm	

P = Portrait FS = Freestanding TBD = To Be Determined
L = Landscape